

Cabinet Refrigerators/ Freezers

Instruction manual



Model:

DL893-A/DL894-A/DL895-A/DL896-A/DL897-A/ DL898-A/DL899-A /CK480-A

Telephone Helpline: 1300225960



Safety Tips

- Position on a flat, stable surface.
- A service agent/qualified technician should carry out installation and any repairs if required. Do not remove any components or service panels on this product.
- Consult Local and National Standards to comply with the following:
 - Health and Safety at Work Legislation
 - Fire Precautions
 - Wiring Regulations
 - Building Regulations
- DO NOT use jet/pressure washers to clean the appliance.
- DO NOT use the appliance outside.
- DO NOT use this appliance to store medical supplies.
- DO NOT use electrical appliances inside the appliance (e.g. heaters, ice cream makers etc.)
- DO NOT stand or support yourself on the base, drawers or doors.
- DO NOT allow oil or fat to come into contact with the plastic components or door seal. Clean immediately if contact occurs.
- Bottles that contain a high percentage of alcohol must be sealed and placed vertically in the refrigerator.
- Always carry, store and handle the appliance in a vertical position and move by holding the base of the appliance.
- Always switch off and disconnect the power supply to the unit before cleaning.
- Keep all packaging away from children. Dispose of the packaging in accordance with the regulations of local authorities.
- If the power cord is damaged, it must be replaced by a POLAR agent or a recommended qualified technician in order to avoid a hazard.

- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
- Polar recommend that this appliance is PAT tested on an annual basis to ensure the product remains safe.

Caution Risk of Fire

 Do not store explosive substances such as aerosol cans with a flammable propellant in this appliance.



Warning: Keep all ventilation openings clear of obstruction. Unit should not be boxed in without adequate ventilation.

- Warning: Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.
- Warning: Do not damage the refrigerant circuit.
- Warning: Do not use electrical appliances inside the food storage compartments of the appliance, unless they are the type recommended by the manufacturer.

Product Description

DL893-A - 600 litre Single Door Stainless Steel Refrigerator

DL894-A - 600 litre Single Door Stainless Steel Freezer

DL895-A - 1200 litre Double Door Stainless Steel Refrigerator

DL896-A - 1200 litre Double Door Stainless Steel Freezer

DL897-A - 1200 litre Double Door White Freezer

DL898-A - 1200 litre Double Door White Refrigerator

DL899-A - 600 litre Single Door White Refrigerator

CK480-A - 600 litre Single Door White Freezer

Introduction

Please take a few moments to carefully read through this manual. Correct maintenance and operation of this machine will provide the best possible performance from your POLAR product.

(AU)

Telephone Helpline: 1300225960

Pack Contents

The following is included:

- POLAR Refrigerator or Freezer
- Keys x 2
- Shelf guides x 6 (Single) / x 12 (Double)
- Shelves x 3 (Single)/x 6 (Double)
- Instruction manual

POLAR prides itself on quality and service, ensuring that at the time of packaging the contents are supplied fully functional and free of damage.

Should you find any damage as a result of transit, please contact your POLAR dealer immediately.

Installation



Note: If the unit has not been stored or moved in an upright position, let it stand upright for approximately 12 hours before operation. If in doubt allow to stand

- Remove the appliance from the packaging. Make sure that all protective plastic film and coatings are thoroughly removed from all surfaces.
- Maintain a distance of 20cm (7 inches) between the unit and walls or other objects for ventilation. NEVER LOCATE NEXT TO OR NEAR A HEAT SOURCE.




feet.

Note: Before using the appliance for the first time, clean the shelves and interior with soapy water.

 Set the brakes on the castors to keep the appliance in position OR Level the appliance by adjusting the screw

Removing the Compressor Safety Band

- The compressor is located on the top of the appliance, and sits on rubber washers. Under normal operating conditions the compressor is allowed to vibrate.
- To avoid damage through excessive motion during transit, a stainless steel safety band is placed over the compressor and screwed into the top of the appliance.
- This safety band and the two screws fixing it to the appliance must be removed before the appliance is turned on.



Lock/Unlock the Doors

A lock is fitted to the doors to ensure foodstuffs are kept secure within your POLAR appliance.

Use the keys provided to lock/unlock the doors.

Fitting the Shelves

- 1. Place one set of shelf guides on either side of the cabinet at the desired height.
- 2. Slide the shelf into place.
- 3. Repeat for the remaining shelves.



Operation

Storing Food

To get the best results from your POLAR appliance, follow these instructions:

- Only store foodstuffs in the appliance when it has reached the correct operating temperature.
- Do not place uncovered hot food or liquid inside the appliance.
- Wrap or cover food where possible.
- Do not obstruct the fans inside the appliance.
- Avoid opening the doors for prolonged periods of time.

Turn On

- 1. Close the door(s) of the appliance.
- 2. Ensure the power switch is set to [**0**] and turn on at the socket.
- 3. Switch on the Power [1]. The current temperature within the appliance is displayed.

Control Panel



To See the Setpoint

Push and immediately release the SET key: the display will show the Setpoint value.

Changing the Setpoint

- 1. Push the **SET** key for more than 2 seconds to change the Setpoint value.
- 2. The value of the set point will be displayed and the COMPRESSOR LED starts blinking.
- 3. To change the Set value push \triangle and \checkmark buttons within 10 seconds.
- To store the new Setpoint push the SET key or wait 10 seconds.

Manual Defrost

The appliance will automatically run a defrost cycle every six hours.



Note: The cycle starts from the time the appliance is initially powered up.

To manually defrost the appliance:

- Press and hold the aux button for more then 2 seconds.
- The defrost cycle will start immediately and the Defrost LED illuminates.



Note: Starting a manual defrost also resets the automatic defrost timer.

The next automatic defrost will start six hours after the manual defrost has finished.

Cleaning, Care & Maintenance



Defrost appliance at least every 3 months, more often if required.

Switch off and disconnect from the power supply before cleaning.

- Clean the interior of the appliance as often as possible.
- Do not use abrasive cleaning agents. These can leave harmful residues.
- Clean the door seal with warm soapy water.
- Always wipe dry after cleaning.
- Do not allow water used in cleaning to run through the drain hole into the evaporation pan.
- Take care when cleaning the rear of the appliance. Sharp edges can cut.
- A POLAR agent or qualified technician must carry out repairs if required.

Telephone Helpline: 1300225960



Stainless Steel Care

To maintain the stainless steel exterior of your Polar item, please consider the following information:

Never:

- Use abrasive Scourers or scrubbing pads, etc.
- Use Chlorinated or acidic detergents.
- Allow anything e.g. food, dirt, cleaning chemicals to remain on the surface for longer than necessary, clean them off right away.
- Allow the surface to remain wet.

Do:

- Clean often.
- Use soft Cloths or plastic Scourers.
- Rub with the grain of the metal, rather than across it.
- Use detergents and polish designed for cleaning Stainless Steel.
- Ensure that the cleaning products are washed off fully and that the steel is left dry.

Cleaning the Condenser

- The condenser is part of the refrigeration system. The condenser requires monthly cleaning.
- Always disconnect power supply before carrying out Routine Maintenance.
- Failure to clean the condenser will reduce the performance and life of your Polar unit and may invalidate your warranty.
- The condenser is located above the refrigeration cabinet. These models have a removable filter which can be cleaned with a vacuum cleaner.



Troubleshooting

If your POLAR appliance develops a fault, please check the following table before making a call to the Helpline or your POLAR dealer.

Fault	Probable Cause	Solution	
The appliance is not working	The unit is not switched on	Check the unit is plugged in correctly and switched on	
	Plug and lead are damaged	Call POLAR agent or qualified Technician	
	Fuse in the plug has blown	Replace the fuse	
	Power supply	Check power supply	
	Internal wiring fault	Call POLAR agent or qualified Technician	



Fault	Probable Cause	Solution	
The appliance turns on, but the temperature is too high/low	Too much ice on the evaporator	Defrost the appliance	
	Condenser blocked with dust	Clean condenser with hose attachment of vacuum	
	Doors are not shut properly	Check doors are shut and seals are not damaged	
	Appliance is located near a heat source or air flow to the condenser is being interrupted	Move the refrigerator to a more suitable location	
	Ambient temperature is too high	Increase ventilation or move appliance to a cooler position	
	Unsuitable foodstuffs are being stored in the appliance	Remove any excessive hot foodstuffs or blockages to the fan	
	Appliance is overloaded	Reduce the amount of food stored in the appliance	
The appliance is leaking water	The appliance is not properly levelled	Adjust the screw feet to level the appliance (if applicable)	
	The discharge outlet is blocked	Clear the discharge outlet	
	Movement of water to the drain is obstructed	Clear the floor of the appliance (if applicable)	
	The water container is damaged	Call POLAR agent or qualified Technician	
	The drip tray is overflowing	Empty the drip tray (if applicable)	
The appliance is unusually loud	The safety band has not been removed	Remove the safety band	
	Loose nut/screw	Check and tighten all nuts and screws	
	The appliance has not been installed in a level or stable position	Check installation position and change if necessary	

Technical Specifications

Model	Voltage	Power	Current	Temperature Range	Capacity (litres)
DL893-A	220-240V 50Hz	255	2.0A	-2°C to 8°C	376
DL894-A	220-240V 50Hz	565	4.9A	-22°C to -18°C	376
DL895-A	220-240V 50Hz	400	3.0A	-2°C to 8°C	681
DL896-A	220-240V 50Hz	800	4.8A	-22°C to -18°C	681
DL897-A	220-240V 50Hz	800	4.8A	-22°C to -18°C	681
DL898-A	220-240V 50Hz	400	3.0A	-2°C to 8°C	681
DL899-A	220-240V 50Hz	255	2.0A	-2°C to 8°C	376
CK480-A	220-240V 50Hz	565	4.9A	-22°C to -18°C	376

Model	Refrigerant	Dimensions H x W x D mm	Weight (kg)
DL893-A	R290 95g	2000 x 680 x 858	145
DL894-A	R290 100g	2000 x 680 x 858	148
DL895-A	R290 110g	2000 x 1340 x 858	195
DL896-A	R290 130g	2000 x 1340 x 858	198
DL897-A	R290 130g	2000 x 1340 x 858	198
DL898-A	R290 130g	2000 x 1340 x 858	195
DL899-A	R290 90g	2000 x 680 x 858	145
CK480-A	R290 90g	2000 x 680 x 858	138

Electrical Wiring

The plug is to be connected to a suitable mains socket.

POLAR appliances are wired as follows:

- Live wire (coloured brown) to terminal marked L
- · Neutral wire (coloured blue) to terminal marked N
- Earth wire (coloured green/yellow) to terminal marked E

This appliance must be earthed.




If in doubt consult a qualified electrician.

Electrical isolation points must be kept clear of any obstructions. In the event of any emergency disconnection being required they must be readily accessible.

Compliance

The product must not be disposed of as household waste. To help prevent possible harm to human health and/or the environment, the product must be disposed of in an approved and environmentally safe recycling process. For further information on how to dispose of this product correctly, contact the product supplier, or the local authority responsible for waste disposal in your area.

POLAR parts have undergone strict product testing in order to comply with regulatory standards and specifications set by international, independent, and federal authorities.





All rights reserved. No part of these instructions may be produced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording or otherwise, without the prior written permission of POLAR.

Every effort is made to ensure all details are correct at the time of going to press, however, POLAR reserve the right to change specifications without notice.

8

DECLARATION OF CONFORMITY

Equipment Type Gastro Refrigerator Single Door Upright - 600Ltr Ventilated

Gastro Freezer Single Door Upright - 600Ltr Ventilated Gastro Refrigerator 2 Door Upright - 1200L Ventilated

Gastro Freezer 2 Door Upright - 1200L Ventilated
Solid Double Door Freezer White Exterior - 1200Ltr Ventilated
Solid Double Door Refrigerator White Exterior - 1200Ltr Ventilated

Gastro Refrigerator Single Door Upright- 600Ltr Ventilated

Cabinet Freezer 600ltr White Exterior

Model DL893-A

DL894-A DL895-A DL896-A DL897-A DL898-A DL899-A CK480-A

Legislation Electrical Safety

Electromagnetic Compatibility

Standards AS/NZS 60335.1:2011 +A1:2012 +A2:2014 +A3:2015 +A4:2017

AS/NZS 60335.2.89:2010 +A1:2013 +A2:2016

EN55014-1:2006 +A1:2009 +A2:2011

EN55014-2:2015 EN61000-3-2:2014 EN61000-3-3:2013

Producer Name Polar

Producer Address 15 Badgally Road,

Campbelltown, NSW 2560

I, the undersigned, hereby declare that the equipment specified above conforms to the above Legislation and Standard(s).

Date 26th April 2019

Signature

Full Name Ashley Hoope

Position Technical & Quality Manager/ Responsible Supplier





http://www.polar-refrigerator.com/

DL893-A-DL899-A_CK480-A_A5_v7_20190513